



Provides an excellent watertight seal  
Adjusts automatically to every shape  
Sealpass is used for protection of pipelines, cables and cable connections  
Very good adhesion on steel, plastics and on uneven surfaces  
Provides corrosion protection

## Features

- Consists of a black EPT-butyl rubber and a brown self-amalgamating butyl rubber petroleum jelly
- Very good adhesion to steel, plastic and both rough and smooth surfaces
- Forms easily to any shape. Does not affect the surface
- Excellent protection against corrosion
- Equipped with a protective film

## Specifications

Thickness EPT-butyl rubber	1mm	ASTM D 1000
Thickness butyl rubber petroleum jelly	1mm	
Total thickness	2mm	
Width	50mm	
Adhesion RVS	1500 g/25mm at 20°C	ASTM D 1000
Adhesion PE	1000 g/25mm at 20°C	ASTM D 1000
Tensile strength	3,0 kg/25mm	ASTM D 1000
Elongation at break	600%	ASTM D 1000
Insulation resistance	1,0 x 10 <sup>15</sup> ohm cm	ASTM D 257
Dielectric strength	33 kV	ASTM D 149
Water absorption	0,1%	ASTM D 570

## Products

Art.nr.	Product Name	Dimensions	Colour	Order unit
81203UK	Sealpass 50mm x 10m	50mm x 10m x 2mm	black/brown	per piece