

# Nitto tape 15 self fusing butyl rubber tape



Nitto 15 is a self fusing rubber tape, widely used for electrical insulation, protection, splicing and termination of 6 to 22KV cables.

Used for termination, splicing & corrosion protection to cables. Completely self-amalgimates in two hours.

## Features

- Excellent vulcanising properties. When the tape is applied with a stretch of 80% , it will be vulcanized in 1 – 2 hours
- No liner and therefore quicker installation time
- No liner waste material
- Excellent electrical properties. High isolation values and break down voltage
- Excellent weather and water resistance
- Fully resistant against moisture, water, and many chemicals

# Nitto tape 15 self fusing butyl rubber tape

## Specifications

Material	Self-fusing butylrubber
colour	black
Elongation at break	at least 550% at 23°C
Breakdown voltage	44 kV/mm

# Nitto tape 15 self fusing butyl rubber tape

## More info

<http://filoform.co.uk/nitto-tape>

## Products

Art.nr.	Product Name	Dimensions	Colour	Order unit
800452UK	Self-fusing butylrubbertape 19mm x 5m x 0,75mm	19mm x 5m x 0,75mm	black	100 rollen /carton
80046UK	Self-fusing butylrubbertape 38mm x 10m x 0,50mm	38mm x 10m x 0,50mm	black	50 rollen / carton