



Re-enterable insulating clear gel designed for the protection of electrical / electronic enclosures, boxes, terminal blocks, trunking, pipes and mechanical parts against water, moisture, dirt, dust, and mechanical shock.

## Features

- Resin can be removed very easily
- Free of iso-cyanates, epoxides and silicones
- Non toxic
- Long Shelf life
- Not classified according to the EC regulations
- Medium viscosity while pouring
- Good adhesion to metals, minerals and many plastics
- Excellent hydrophobic behaviour

## Specifications

Properties	Unit	Value
Potlife (process time) 20°C	minutes	20
Gel-time 20°C	minutes	50
Viscosity 20°C	cps	1000
Exothermic peak (ASTM D2471)	°C	28
Density	g / cm <sup>3</sup>	0.91
Elongation at break	%	95
Temperature resistance	°C	80°C (short 120°C)
Corrosion of copper (MS 17000, 1139)		non corrosive
Insulation resistance at 500 V DC	ohm	1.2 x 10 <sup>12</sup>
Volume resistivity bij 500 V DC	ohm.cm	0.6 x 10 <sup>13</sup>
Water absorption (ASTM D570)	%	0.36
Water sensitivity (TA-NWT-000354)	%	0
Chemical resistant against		2n, H2SO4, CaCO3
colour		Transparent amber
Shelf life		18 months

## More info

[Download: Mixing instructions](#)



## Products

Art.nr.	Product Name	Order unit
210250	Filogel gel resin 250ml	10 pcs/carton
211000	Filogel gel resin 1000ml	3 pcs/carton