

# Wrap around sleeves



Cable joints and cable terminations  
Cables up to 1kV  
Telecommunication  
For indoor and outdoor use:  
underground, above ground, under water and in cable ducts

## Features

- Polyolefine cross linked
- Fast recovery
- Continuous temperature -40°C till +125°C
- Excellent resistance against UV and chemicals
- Corrosion resistant
- Colour: black

## Specifications

Material	Polyofine	
Shrink temperature	> 125°C	
Continuous temperature	-40°C till +125°C	
Dielectric strength	≥ 22 kV/mm	ASTM D 149-97a
Volume resistivity	> 1 x 10 <sup>14</sup> ohm cm	ASTM D 257-98
Heatshock (225°C)	No damage	ASTM D 2671-98
Tensile strength	≥ 18 Mpa	ASTM D 638-98
Elongation at break	≥ 500%	ASTM D 638-98
Water absorbtion	≤ 0.5%	ISO 62-86
Mould resistance	No growth	ASTM G21-96 / ASTM D 638-98
Oil resistance	Excellent	ISO 175-99

# Wrap around sleeves

## Products

Art.nr.	Product Name	Wall thickness after shrink (mm)	Order unit
505540	Wrap around sleeve 126.0 > 47.0mm	2,0	per piece
505530	Wrap around sleeve 91.0 > 33.0mm	2,0	per piece
505520	Wrap around sleeve 68.0 > 24.0mm	2,0	per piece
505510	Wrap around sleeve 46.0 > 14.0mm	2,0	per piece
505500	Wrap around sleeve 30.0 > 6.0mm	2,0	per piece