

Wrap around tape



Wrap around tape ensures a liquid tight covering when wrapped around the mesh, creating a secure means for injecting the resin into injection joints. Can be used for the binding of cables and pipes.

Features

- Excellent, elastic 'elongation at break' properties
- Excellent processability under high and low temperatures
- Good adhesion even under moist conditions
- Flame retardent
- Excellent electrical insulation
- Various dimensions

Specifications

Material	(soft) PVC
Thickness	0.19mm
Adhesive type	synthetic rubber
Adhesion	400 gr./25mm
Unrolling force	500 gr./25mm
Tensile strenght	10.5 kg/25mm
Elongation at break	240%
Breakdown voltage	9 kV
Min. application temperature	-10°C
Temperature range	-40°C till +90°C
Colour	transparent

Wrap around tape

Products

Art.nr.	Product Name	Dimensions	Colour	Order unit
80467UK	Wrap-around tape 38mm x 20m transparent	38mm x 20m x 0,19mm	transparent	64 pcs/carton
910110	Wrap-around tape 50mm x 10m transparent	50mm x 10m x 0,19mm	transparent	80 pcs/carton
910120	Wrap-around tape 50mm x 20m transparent	50mm x 20m x 0,19mm	transparent	48 pcs/carton
800350.5UK	Nitto tape 21, 25mm x 20m transparent	25mm x 20m x 0,19mm	transparent	128 pcs/carton