

Branch Joints



Branch cast resin cable joints are suitable for plastic and paper insulated LV cables. These joints are suitable for use in power, telecoms and signalisation. The joints are approved in accordance with the standard DIN EN 50393 (VDE 0278-393):2006-11

Designed for UK armoured cables to allow plenty of room to work.

Features

- The cast resin joints correspond to DIN VDE 0278 and can be used on all polymeric- and paper-insulated cables
- With hydrolysis-resistant PUR-cast resin
- Longitudinal and cross-waterproof
- High quality polycarbonate moulds
- Transparent 2-piece, cylindrical shells with pre-installed sealing strips
- Illustrated mounting instruction
- Simple and fast fitting
- Saves time and costs

Specifications

1.5mm ²	N/A	MB 6	MB 6	MB 6	MB 6*
2.5mm ²	N/A	MB 6	MB 6	MB 6	MB 6*
4mm ²	N/A	MB 6	MB 6	MB 6	MB 6*
6mm ²	N/A	MB 6	MB 6	MB 6	MB 16*
10mm ²	N/A	MB 6	MB 16	MB 16	MB 16*
16mm ²	N/A	MB 16	MB 16	MB 16	MB 35*
25mm ²	N/A	MB 35	MB 35	MB 35	MB 35*
35mm ²	N/A	MB 35	MB 35	MB 35	MB 70*
50mm ²	MB 35*	MB 35*	MB 70*	MB 70*	MB 70*
70mm ²	MB 35*	MB 70	MB 70*	MB 70*	MB 120*
95mm ²	MB 70*	MB 70*	MB 120*	MB 120*	MB 120*
120mm ²	MB 70*	MB 120*	MB 120*	MB 120*	MB 300*
150mm ²	MB 70*	MB 120*	MB 120*	MB 185*	MB 300*
185mm ²	MB 70*	MB 120*	MB 300*	MB 300*	MB 300*
240mm ²	MB 120*	MB 300*	MB 300*	MB 300*	MB 300*
300mm ²	MB 120*	MB 300*	MB 300*	MB 300*	N/A

Size of conductor

Products

Art.nr.	Product Name	Cable Diameter (mm)	Dimensions (mm)	Order unit
MB6	MB6	Ø 12 - 24	220 x 76	per piece
MB16	MB16	Ø 09 - 25	335 x 120	per piece
MB35	MB35	Ø 08 - 30	420 x 135	per piece
MB70	MB70	Ø 15 - 40	485 x 120	per piece
MB120	MB120	Ø 20 - 55	655 x 165	per piece
MB300	MB300	Ø 65 - 75	900 x 220	per piece