


# FiloSeal+HD Duct Seal



Duct sealing system FiloSeal+HD is an engineered universal solution for sealing larger heavy cables and pipes in ducts, boreholes or transit frames.

Up to 2 bar Pressure Resistance  
100Kg pulling Force on the cables when sealed  
10xd at 45°, with 1 bar pressure bending test



## Features

- Flexible, one component, adhesive and sealing compound in a cartridge - (310ml)
- Kits are complete with backing and mastic to fill an empty duct of the quoted kit size
- High levels of Gas and Water tightness
- Excellent adhesion, applicable to all common building materials
- Shows Fire resistance properties
- Resistant against Water, Alkaline, Chemical agents
- Resistant to termites (*Mastotermes darwiniensis*) Northern Australian termites
- Resistant to Rats
- Resistant to Hydrogen Sulphide / Methane and many other Gases (NedLab)
- Non-corrosive
- Solvent-free
- Shock absorbing
- Non-toxic, neutral and almost odourless
- Also suitable for limiting the EX-zones during transitions (observe chemical resistance)
- Complies with 2011 NEC Articles 225.27, 230.8, 300.5(G), 300.7 (A) on Raceway Seals, and 501.15 (B)(2)
- Suitable for any shaped duct/borehole/opening
- WIMES Compliant (3.02 2013 6.4.3.2 b)
- Quick and easy installation
- A complete kit
- Seals all known materials, PVC & PE sheathed cables, PILC, (HD) PE pipes
- Engineering duct sealing solution
- Suitable for renovations, can be installed retrospectively
- Over 25 years of operational experience

## Specifications

# FiloSeal+HD Duct Seal

Density	1.2 gr/cm <sup>3</sup>	
Pressure	up to 2 bar	
Pulling Force	100kg (1000 newtons)	
Bend Test	10xd at 45°, with 1 bar pressure	
Flow	< 2mm	ISO 7390
Colour	red-brown	
Skin over time (23C/55%RH)	± 15 minutes	
Curing	3 mm / 24 hours	
Hardness	30 shore A	DIN 53505
Elongation	100%	DIN 53504
Tensile strength	0.8 N/mm <sup>2</sup>	DIN 53504
Operating temperature	+5°C tot +40°C	
Temperature resistance	-40°C tot +120°C	

Kits are complete with backing and mastic to fill an empty duct of the quoted kit size

## More info

[Download: FiloSeal+ disclaimer](#)

## Products

Art.nr.	Product Name	Duct diameter min.-max. (mm)	Order unit
280010	FiloSeal+HD - 75mm > 110mm	Ø 110 max.	per piece
280020	FiloSeal+HD - 125mm > 160mm	Ø 160 max.	per piece
280030	FiloSeal+HD - 180mm	Ø 180 max.	per piece
280040	FiloSeal+HD - 200mm	Ø 200 max.	per piece
280050	FiloSeal+HD - 225mm	Ø 225 max.	per piece
280060	FiloSeal+HD - 250mm	Ø 250 max.	per piece