


Indoor Three Core 6/10(12)kV



6/10(12)kv - Three core Filoform Medium Voltage Heatshrink Termination Kits are tested in accordance with CENELEC 629.1.S2 & IEC 60502-4, and suitable for Indoor applications up to 6/10(12)kv.

The Filoform range enables the installer to offer a complete solution, utilizing compression or mechanical lugs; and XLPE and EPR cable sheaths.

The Filoform range of Terminations is fully RoHS compliant.

Features

- Right-Angle Insulating Barrier Boots
- Straight Insulating Barrier Boots
- Universal (Push-on) Insulating Barrier Boots
- Bolted Top-Hat Glands for 3-Core SWA
- Compression Lugs
- Mechanical Lugs
- Pole Top Mounting Brackets and Insulators

Indoor Three Core 6/10(12)kV

Products

Art.nr.	Product Name	Cable Diameter (mm)	Core min. (mm)	Core max. (mm ²)	Order unit
HKIT-12/3×25-50-450	HS Indoor Termination 6/10(12)kV - 3×25-50mm ² length 450	Ø 12.0 - 16.0	25	50	per piece
HKIT-12/3×70-150-450	HS Indoor Termination 6/10(12)kV - 3×70-150mm ² length 450	Ø 17.6 - 22.8	70	150	per piece
HKIT-12/3×185-300-450	HS Indoor Termination 6/10(12)kV - 3×185-300mm ² length 450	Ø 24.0 - 31.0	185	300	per piece
HKIT-12/3×400-500-450	HS Indoor Termination 6/10(12)kV - 3×400-500mm ² length 450	Ø 31.5 - 37.0	400	500	per piece